




Floatglass EN 572-9



**Scheuten**  
see it. feel it


## DECLARATION OF PERFORMANCE (CPR 305/2011)

DoP-572-9-2021-01

1. **Product-type:** Scheuten Float – Scheuten Super White
2. **Intended use:** Floatglass in buildings and construction works
3. **Manufacturer:** Scheuten Base Glass BV  
Magelhaesweg 10  
NL-5928 LN Venlo
4. **Authorized representative:** -
5. **System of AVCP:** System 3
6. **Harmonized standard:** EN 572-9:2004  
**Notified Bodies:** NB-Nr.: 0063, 0074, 0336, 0432, 0757, 1166, 1174, 1231, 1234, 1322, 1343, 1488, 1694, 1717, 1750, 1812, 2264, 2509
7. **Declared performances:**



Floatglass EN 572-9



**Scheuten**  
see it. feel it

Scheuten Float									
EN 572-9: 2004	Essential characteristics:	AVCP Systems	3 mm	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
4.2.2.1	Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.2	Reaction to fire	3,4	A1	A1	A1	A1	A1	A1	A1
4.2.2.3	External fire performance	3,4	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.4	Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.5	Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.6	Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.7	Pendulum Body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.8	Resistance against sudden temperature changes and temperatures differentials [K]	4	40	40	40	40	40	40	40
4.2.2.9	Resistance against wind, snow, permanent and imposed load resistance [Mpa]	4	45	45	45	45	45	45	45
4.2.2.10	Direct airborne sound insulation $R_w$ (C;C <sub>tr</sub> ) [dB]	3	28 (-1;-4)	29 (-2;-3)	30 (-1;-2)	31 (-2;-3)	32 (-2;-3)	33 (-2;-3)	34 (-1;-2)
4.2.2.11	U-Value (Thermal properties) [W/m <sup>2</sup> K]	3	5,8	5,8	5,7	5,7	5,6	5,6	5,5
4.2.2.11	Normal emissivity $\epsilon_n$ of coating side	3	0,89	0,89	0,89	0,89	0,89	0,89	0,89
4.2.2.12	Light transmittance (Coating on position 1) Light reflectance outside Light reflectance inside	3	$\tau_v = 91$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 91$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 90$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 90$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 89$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 89$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 88$ $\rho_v = 8$ $\rho'_v = 8$
4.2.2.13	Total solar energy transmittance (Coating on position 1) Solar direct transmittance Solar direct reflectance outside Solar direct reflectance inside	3	$g = 89$ $\tau_e = 88$ $\rho_e = 8$ $\rho'_e = 8$	$g = 88$ $\tau_e = 87$ $\rho_e = 8$ $\rho'_e = 8$	$g = 88$ $\tau_e = 86$ $\rho_e = 8$ $\rho'_e = 8$	$g = 87$ $\tau_e = 85$ $\rho_e = 8$ $\rho'_e = 8$	$g = 86$ $\tau_e = 83$ $\rho_e = 8$ $\rho'_e = 8$	$g = 84$ $\tau_e = 82$ $\rho_e = 7$ $\rho'_e = 7$	$g = 83$ $\tau_e = 80$ $\rho_e = 7$ $\rho'_e = 7$
	Durability	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD




## Floatglass EN 572-9



Scheuten Float				
EN 572-9: 2004	Essential characteristics:	AVCP Systems	15 mm	19 mm
4.2.2.1	Resistance to fire	1	NPD	NPD
4.2.2.2	Reaction to fire	3,4	A1	A1
4.2.2.3	External fire performance	3,4	NPD	NPD
4.2.2.4	Bullet resistance	1	NPD	NPD
4.2.2.5	Explosion resistance	1	NPD	NPD
4.2.2.6	Burglar resistance	3	NPD	NPD
4.2.2.7	Pendulum Body impact resistance	3	NPD	NPD
4.2.2.8	Resistance against sudden temperature changes and temperatures differentials [K]	4	40	40
4.2.2.9	Resistance against wind, snow, permanent and imposed load resistance [Mpa]	4	45	45
4.2.2.10	Direct airborne sound insulation $R_w$ (C;C <sub>tr</sub> ) [dB]	3	36 (-1;-2)	38 (-2;-4)
4.2.2.11	U-Value (Thermal properties) [W/m <sup>2</sup> K]	3	5,4	5,3
4.2.2.11	Normal emissivity $\epsilon_n$ of coating side	3	0,89	0,89
4.2.2.12	Light transmittance (Coating on position 1) Light reflectance outside Light reflectance inside	3	$\tau_v = 85$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 83$ $\rho_v = 8$ $\rho'_v = 8$
4.2.2.13	Total solar energy transmittance (Coating on position 1) Solar direct transmittance Solar direct reflectance outside Solar direct reflectance inside	3	$g = 76$ $\tau_e = 71$ $\rho_e = 7$ $\rho'_e = 7$	$g = 73$ $\tau_e = 67$ $\rho_e = 6$ $\rho'_e = 6$
	Durability	3	NPD	NPD



Floatglass EN 572-9



**Scheuten**  
see it. feel it

Scheuten Super White									
EN 572-9: 2004	Essential characteristics:	AVCP Systems	3 mm	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
4.2.2.1	Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.2	Reaction to fire	3,4	A1	A1	A1	A1	A1	A1	A1
4.2.2.3	External fire performance	3,4	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.4	Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.5	Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.6	Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.7	Pendulum Body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4.2.2.8	Resistance against sudden temperature changes and temperatures differentials [K]	4	40	40	40	40	40	40	40
4.2.2.9	Resistance against wind, snow, permanent and imposed load resistance [Mpa]	4	45	45	45	45	45	45	45
4.2.2.10	Direct airborne sound insulation $R_w$ (C;C <sub>tr</sub> ) [dB]	3	28 (-1;-4)	29 (-2;-3)	30 (-1;-2)	31 (-2;-3)	32 (-2;-3)	33 (-2;-3)	34 (-1;-2)
4.2.2.11	U-Value (Thermal properties) [W/m <sup>2</sup> K]	3	5,8	5,8	5,7	5,7	5,6	5,6	5,5
4.2.2.11	Normal emissivity $\epsilon_n$ of coating side	3	0,89	0,89	0,89	0,89	0,89	0,89	0,89
4.2.2.12	Light transmittance (Coating on position 1) Light reflectance outside Light reflectance inside	3	$\tau_v = 92$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 92$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 91$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 91$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 91$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 91$ $\rho_v = 8$ $\rho'_v = 8$	$\tau_v = 91$ $\rho_v = 8$ $\rho'_v = 8$
4.2.2.13	Total solar energy transmittance (Coating on position 1) Solar direct transmittance Solar direct reflectance outside Solar direct reflectance inside	3	$g = 91$ $T_e = 91$ $\rho_e = 8$ $\rho'_e = 8$	$g = 91$ $T_e = 91$ $\rho_e = 8$ $\rho'_e = 8$	$g = 91$ $T_e = 90$ $\rho_e = 8$ $\rho'_e = 8$	$g = 90$ $T_e = 90$ $\rho_e = 8$ $\rho'_e = 8$	$g = 90$ $T_e = 89$ $\rho_e = 8$ $\rho'_e = 8$	$g = 90$ $T_e = 89$ $\rho_e = 8$ $\rho'_e = 8$	$g = 89$ $T_e = 88$ $\rho_e = 8$ $\rho'_e = 8$
	Durability	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD

The performance of the product (1) identified above is in conformity with the set of declared performance/s.  
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer (3) identified above.

Signed for and on behalf of the manufacturer by:

Dhr. R. Geerlings, (CCO) Scheuten Glass Holding b.v.

Venlo, 1 January 2021

